

## EPDM



EPDM rubber sheets are moderately well weather resistant (ozone, heat, cold) and have a good resistance to aging. Also applicable for some chemicals. Two smooth surfaces.

Temperature: -20°C to +85°C

- Hardness: 65 °Shore +/-5
- Density: 1,5 g/cm<sup>3</sup>
- Tensile strength: 4 Mpa
- Elasticity at rupture: 250 %

### Applications

hot water, car industry

| Ref        | Thickness<br>(mm) | Width<br>(m) | Length<br>(m) |
|------------|-------------------|--------------|---------------|
| RPEPDM0100 | 1                 | 1,40         | 10,00         |
| RPEPDM0200 | 2                 | 1,40         | 10,00         |
| RPEPDM0300 | 3                 | 1,40         | 10,00         |
| RPEPDM0400 | 4                 | 1,40         | 10,00         |
| RPEPDM0500 | 5                 | 1,40         | 10,00         |
| RPEPDM0600 | 6                 | 1,40         | 10,00         |
| RPEPDM0800 | 8                 | 1,40         | 5,00          |
| RPEPDM1000 | 10                | 1,40         | 5,00          |
| RPEPDM1500 | 15                | 1,40         | 5,00          |

Product ID: 31040

Source URL: <https://www.alfaflex.com/en/products/30000/31000/epdm-0>