

Opal



PVC hose reinforced by an hard pvc spiral, with food grade quality, suitable for the suction and delivery of a multitube of media and food stuffs. Opal is very easy to handle even at low temperatures.

Temperature: -10°C to +60°C

Construction: transparent pvc with food grade quality with an embedded hard white pvc spiral in the hose wall, smooth inside.

Certificat: IANESCO 10617 dated 12/09/2008

Remarks: transport of food products following simulations A, B and C of the certificat, with the exception of alcoholic solutions > 15°

ATTENTION: forbidden for the use with fatty food stuffs (vegetal oils, milk, ...)

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Vacuum (mH2O)	Coil length (m)
NE020	20	2,9	250	100	6	7	25* - 50
NE025	25	2,9	310	135	6	7	25* - 50
NE030	30	3	370	140	6	7	25* - 50
NE032	32	3,1	400	150	6	7	25* - 50
NE035	35	3,2	490	165	6	7	25* - 50
NE038	38	3,4	530	180	6	7	25* - 50
NE040	40	3,6	560	190	6	7	25* - 50
NE045	45	3,8	680	210	5	7	25* - 50
NE050	50	4,1	810	220	5	7	25* - 50
NE055	55	4,2	895	250	5	7	25* - 50
NE060	60	4,2	975	280	5	7	25* - 50
NE063	63	4,3	1050	300	4	7	25* - 50
NE070	70	4,6	1200	325	4	7	25* - 50
NE075	75	4,8	1390	345	4	7	25* - 50
NE080	80	5,2	1580	360	3	7	25* - 50
NE090	90	5,5	1850	425	3	7	25* - 50
NE100	100	6	2200	480	3	7	25* - 50
NE110	110	6,1	2530	525	3	6	25*
NE120	120	6,2	2800	670	2	6	25*

Product ID: 14050

Source URL: <https://www.alfaflex.com/en/products/10000/14000/opal-1>