

AX Dry Cement S&D



Antistatic NR/SBR suction and delivery hose for conveying and handling dry abrasive bulk materials at low pressure (10 bar). Suitable for applications in silos and tank trucks.

Temperature: -40°C to +70°C

- **Tube:** black smooth anti static NR/SBR rubber
- **Reinforcement:** high tenacity textile yarn and embedded steel helix
- **Cover:** black antistatic NR/SBR rubber with cloth impression, abrasion and weathering resistant

Abrasion loss of the tube: rubber compound according to DIN 53516 70±5 mm³

Remark: Other diameters, pressure ratings and inner tube rubber quality (higher abrasion resistance, light coloured para rubber) available on request.

Applications

cement, sand, gravel, chalk, lime, ...

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Vacuum (mH20)	Bending Radius (mm)	Coil length (m)
TBX050	51 x 65	1.920	10	30	0,9	300	40 - 61
TBX065	65 x 79	2.430	10	30	0,9	380	40 - 61
TBX075	76 x 92	3.280	10	30	0,9	450	40 - 61
TBX090	90 x 110	3.800	10	30	0,9	540	40 - 61
TBX100	102 x 118	4.800	10	30	0,9	610	40 - 61
TBX110	110 x 129	5.600	10	30	0,8	660	40 - 61
TBX115	115 x 135	5.800	10	30	0,8	700	40 - 61
TBX125	127 x 147	6.800	10	30	0,8	760	40 - 61
TBX125	152 x 174	11.000	10	30	0,8	920	40 - 61
TBX200	203 x 229	16.300	10	30	0,7	1220	40

Product ID: 40110

Source URL: <https://www.alfaflex.com/en/products/40000/40100/ax-dry-cement-sd-0>